

FILTER CARTRIDGES

for multi-cartridge filters

POLYPROPYLENE CARTRIDGES

Melt-blown extruded polypropylene cartridges with rigid polypropylene inner support, double opened end (DOE) version. The cartridges are not heat-sanitised. Maximum pressure difference the cartridges can withstand at 20 °C: 2 bar.

Maximum recommended pressure difference for replacement: 1 bar. Other filtration grades (1, 3, 5, 30, 75, 90 µm) are also available on request.



TECHNICAL DATA

Code	Height inches	Degree of filtration µm	Efficiency %	Maximum temperature °C	Scope* L/h	Surface filter m ²
WT0006200	9" ¾	10	95	60	1500	0,05
WT0006201		20			1900	
WT0006202		50			2100	
WT0006203	20"	10			2300	0,1
WT0006204		20			2500	
WT0006205		50			2700	
WT0006206	40"	10			4000	0,2
WT0006207		20				
WT0006208		50				

* Max. flow rate in l/h of water at 20°C and pressure difference 0.15 bar.

FILTER CARTRIDGES

for multi-cartridge filters

NYLON NET CARTRIDGES

Washable monofilament nylon mesh cartridges complete with flat PVC seals, double opened end (DOE) version. The cartridges are not heat-sanitised. Maximum pressure difference the cartridges can withstand at 20 °C: 2 bar. Maximum recommended pressure difference for replacement: 1 bar.



TECHNICAL DATA

Code	Height* thumbs	Degree of filtration µm	Efficiency %	Maximum temperature °C	Scope** L/h	Surface filter m ²
WT0006250	9" ¾	80	75	60	3500	0,05
WT0006251	20"				7000	0,1

* The 20" model consists of two 9"¾ elements.

** Max. flow rate in l/h of water at 20°C and pressure difference 0.15 bar.